


Blind rivet nuts alu


Material: AlMg 3

Standard Dome head




	Rivet body D, x L mm	Grip range mm	Part no.	Quantity per box
M 4 Hole Ø: 6.1 mm	6 x 11,0	0,25 - 3,0	641 0030	A 500
	6 x 13,0	2,5 - 4,5	641 0073	"
M 5 Hole Ø: 7.1 mm	7 x 11,5	0,25 - 3,0	641 0138	A 500
	7 x 13,5	2,5 - 5,0	641 0170	"
M 6 Hole Ø: 9.1 mm	9 x 15,5	0,25 - 3,5	641 0235	A 250
	9 x 18,0	3,0 - 5,5	641 0278	"
M 8 Hole Ø: 11.1 mm	11 x 17,0	0,25 - 3,5	641 0332	A 100
	11 x 20,0	3,0 - 6,0	641 0367	"
M 10 Hole Ø: 12.1 mm	12 x 17,5	0,25 - 3,5	641 0456	A 100
	12 x 20,5	3,0 - 6,0	641 0480	"

Small head



	Rivet body D, x L mm	Grip range mm	Part no.	Quantity per box
M 4 Hole Ø: 6.1 mm	6 x 12,0	0,5 - 3,0	641 0553	A 500
M 5 Hole Ø: 7.1 mm	7 x 12,5	0,5 - 3,0	641 0650	A 500
M 6 Hole Ø: 9.1 mm	9 x 15,5	0,5 - 3,5	641 0758	A 250
M 8 Hole Ø: 11.1 mm	11 x 17,0	0,5 - 3,5	641 0766	A 100

Countersunk (90°)



	Rivet body D, x L mm	Grip range mm	Part no.	Quantity per box
M 4 Hole Ø: 6.1 mm	6 x 12,0	1,5 - 3,5	641 2017	A 500
	6 x 13,5	3,0 - 5,0	641 2041	"
M 5 Hole Ø: 7.1 mm	7 x 13,5	1,5 - 4,0	641 2130	A 500
	7 x 15,5	3,5 - 6,0	641 2149	"
M 6 Hole Ø: 9.1 mm	9 x 17,0	1,5 - 4,5	641 2238	A 250
	9 x 19,0	4,0 - 6,5	641 2246	"
M 8 Hole Ø: 11.1 mm	11 x 18,5	1,5 - 4,5	641 2335	A 100
	11 x 20,5	4,0 - 6,5	641 2343	"
M 10 Hole Ø: 12.1 mm	12 x 19,0	1,5 - 4,5	641 2432	A 100
	12 x 21,0	4,0 - 6,5	641 2440	"


The maximum tightening torque and the threaded breaking force and shear strengths for all blind rivet nuts can be found on pages 160 and 161.

For head diameters, please report to page 171.

Blind rivet nuts steel splined


Material: Steel, zinc-plated

Standard Dome head




	Rivet body D, x L mm	Grip range mm	Part no.	Quantity per box
M 4 Hole Ø: 6.1 mm	6 x 11,0	0,25 - 3,0	642 0052	A 500
	6 x 13,0	2,5 - 4,5	642 0095	"
M 5 Hole Ø: 7.1 mm	7 x 11,5	0,25 - 3,0	642 0176	A 500
	7 x 13,5	2,5 - 5,0	642 0214	"
M 6 Hole Ø: 9.1 mm	9 x 15,5	0,25 - 3,5	642 0273	A 250
	9 x 18,0	3,0 - 5,5	642 0338	"
M 8 Hole Ø: 11.1 mm	11 x 17,0	0,25 - 3,5	642 0397	A 100
	11 x 20,0	3,0 - 6,0	642 0427	"
M 10 Hole Ø: 12.1 mm	12 x 17,5	0,25 - 3,5	642 0494	A 100
	12 x 20,5	3,0 - 6,0	642 0524	"

Small head



	Rivet body D, x L mm	Grip range mm	Part no.	Quantity per box
M 4 Hole Ø: 6.1 mm	6 x 12,0	0,25 - 3,0	642 0613	A 500
M 5 Hole Ø: 7.1 mm	7 x 12,5	0,25 - 3,0	642 0710	A 500
M 6 Hole Ø: 9.1 mm	9 x 15,5	0,25 - 3,5	642 0818	A 250
M 8 Hole Ø: 11.1 mm	11 x 17,0	0,25 - 3,5	642 0826	A 100

Countersunk (90°)



	Rivet body D, x L mm	Grip range mm	Part no.	Quantity per box
M 4 Hole Ø: 6.1 mm	6 x 12,0	1,5 - 3,5	642 2012	A 500
	6 x 13,5	3,0 - 5,0	642 2047	"
M 5 Hole Ø: 7.1 mm	7 x 13,5	1,5 - 4,0	642 2144	A 500
	7 x 15,5	3,5 - 6,0	642 2152	"
M 6 Hole Ø: 9.1 mm	9 x 17,0	1,5 - 4,5	642 2233	A 250
	9 x 19,0	4,0 - 6,5	642 2241	"
M 8 Hole Ø: 11.1 mm	11 x 18,5	1,5 - 4,5	642 2330	A 100
	11 x 20,5	4,0 - 6,5	642 2349	"
M 10 Hole Ø: 12.1 mm	12 x 19,0	1,5 - 4,5	642 2438	A 100
	12 x 21,0	4,0 - 6,5	642 2446	"

The maximum tightening torque and the threaded breaking force and shear strengths for all blind rivet nuts can be found on pages 160 and 161.

For head diameters, please report to page 171.