


Blind rivet nuts Stainless steel A2 half hexagonal


Material: Stainless steel A2 1.4567

Standard Dome head



	Rivet body D, x L mm	Grip range mm	Part no.	Quantity per box
M 4 SW6 +0,1	6 x 11,0	0,5 - 2,0	643 4007	A 500
M 5 SW7 +0,1	7 x 12,0	0,5 - 3,0	643 4015	"
M 6 SW9 +0,1	9 x 15,5	0,5 - 3,0	643 4024	A 250
M 8 SW11 +0,1	11 x 17,0	0,5 - 3,0	643 4210	A 100

Small head



	Rivet body D, x L mm	Grip range mm	Part no.	Quantity per box
M 4 SW6 +0,1	6 x 11,0	0,5 - 2,0	643 4309	A 500
M 5 SW7 +0,1	7 x 12,0	0,5 - 3,0	643 4317	"
M 6 SW9 +0,1	9 x 15,5	0,5 - 3,0	643 4325	A 250
M 8 SW11 +0,1	11 x 17,0	0,5 - 3,0	643 4333	A 100


Material surcharge will be added at a daily rate

The maximum tightening torque and the threaded breaking force and shear strengths for all blind rivet nuts can be found on pages 160 and 161. For head diameters, please report to page 171.

Blind rivet nuts Stainless steel A4


Material: Stainless steel A4 1.4578

Standard Dome head




	Rivet body D, x L mm	Grip range mm	Part no.	Quantity per box
M 4 Hole Ø: 6.1 mm	6 x 11,0	0,25 - 3,0	644 0440	A 500
	6 x 13,0	2,5 - 4,0	644 0490	"
M 5 Hole Ø: 7.1 mm	7 x 11,5	0,25 - 3,0	644 0510	"
	7 x 13,5	2,5 - 4,5	644 0550	"
M 6 Hole Ø: 9.1 mm	9 x 15,5	0,25 - 3,5	644 0012	A 250
	9 x 18,0	3,0 - 5,5	644 0011	"
M 8 Hole Ø: 11.1 mm	11 x 17,0	0,25 - 3,5	644 1010	A 100
	11 x 20,0	3,0 - 6,0	644 1060	"

Small head



	Rivet body D, x L mm	Grip range mm	Part no.	Quantity per box
M 4 Hole Ø: 6.1 mm	6 x 12,0	0,25 - 3,0	644 0480	A 500
	7 x 12,5	0,25 - 3,0	644 0520	"
M 6 Hole Ø: 9.1 mm	9 x 15,5	0,25 - 3,5	644 0015	A 250
	11 x 17,0	0,25 - 3,5	644 1020	A 100

Countersunk



	Rivet body D, x L mm	Grip range mm	Part no.	Quantity per box
M 4 Hole Ø: 6.1 mm	6 x 12,0	1,5 - 3,0	644 0470	A 500
	6 x 13,0	2,5 - 4,0	644 0495	"
M 5 Hole Ø: 7.1 mm	7 x 13,5	1,5 - 4,0	644 0560	"
	7 x 15,5	3,5 - 6,0	644 0570	"
M 6 Hole Ø: 9.1 mm	9 x 17,0	1,5 - 4,5	644 0014	A 250
	9 x 18,5	4,0 - 6,0	644 0013	"
M 8 Hole Ø: 11.1 mm	11 x 18,5	1,5 - 4,5	644 1050	A 100
	11 x 20,0	4,0 - 6,0	644 1070	"

Material surcharge will be added at a daily rate

The maximum tightening torque and the threaded breaking force and shear strengths for all blind rivet nuts can be found on pages 160 and 161. For head diameters, please report to page 171.